

# **DINO GRIP FLAT SHEET**

## **Data Sheet**

### **DESCRIPTION**

Dino Grip Flat Sheet is a high performance safety Flat Sheet made from high quality GRP (glass reinforced plastic) / FRP (fibre reinforced plastic). They are designed to be installed on any flat surface to provide an instant non-slip surface.

### **CHARACTERISTICS**

- Slip Resistant Surface
- Class 1 Flame Spread Non Sparking
- Corrosion Resistant
- Lightweight
- Non Metallic
- Tough & Durable
- Can be Cut to Size
- Ouick Installation

#### **APPLICATIONS**

Ideal for the installation on any surface to provide an instant non-slip surface.

### TECHNICAL DATA

Description	Slip Resistant Decking Profiles
Top Finish	Carbon and Silicon Grip Top Surface
Stock Colors	Black, Yellow and Grey
Thickness	Nominally 0.16" Thick
Chemical Resistance	Different Chemical Resistance Available, Please Call our Technical Department for Advice
Panel Size	8ft x 4ft
Flat Sheet Weight	55 Lbs
Service Temperatures	-4°F to + 176°F
Load capabilities	Credited with no load bearing strength
Design Life	10+ Years (subject to traffic analysis)
General Use	Standard Pedestrian Traffic

### **SLIP RESISTANT LEVELS**

Measured using the Pendulum test method (Four S rubber slider / 96 Slider) - standard simulated shoe sole.

Top Surface	Dry Reading	Wet Reading
Standard Grit Surface	80	75

The Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians.

Four S Pendulum Value	Potential For Slip	
Above 65	Extremely Low	
35 to 65	Low	
25 to 65	Moderate	
25 and Below	High	

To ensure that the above slip resistant levels are maintained the Flat Sheet should be kept clean in accordance with our cleaning guide and tips.

Richco International | Tele: 1-888-848-4157 | Email: info@dinogrip.com