



# DINO GRIP FLAT SHEET

## Data Sheet

### DESCRIPTION

Dino Grip Flat Sheet is a high performance safety Flat Sheet made from high quality GRP (glass reinforced plastic) / FRP (fibre reinforced plastic). They are designed to be installed on any flat surface to provide an instant non-slip surface.

### CHARACTERISTICS

- Slip Resistant Surface
- Impact Resistant
- Class 1 Flame Spread - Non Sparking
- Corrosion Resistant
- Lightweight
- Non Metallic
- Tough & Durable
- Can be Cut to Size
- Quick Installation
- Manufactured to ISO 9001

### APPLICATIONS

Ideal for the installation on any surface to provide an instant non-slip surface.

### TECHNICAL DATA

Description	Slip Resistant Decking Profiles
Top Finish	Carbon and Silicon Grip Top Surface
Stock Colours	Brown
Thickness	Nominally 3-4mm Thick
Chemical Resistance	Different Chemical Resistance Available, Please Call our Technical Department for Advice
Panel Size	2400mm x 1200mm
Landing Cover Weight	8.1kg
Service Temperatures	-20°c to + 80°c
Load capabilities	Credited with no load bearing strength
Design Life	10+ Years (subject to traffic analysis)
General Use	Standard Pedestrian Traffic

### SLIP RESISTANT LEVELS

Measured using the Pendulum test method (Four S rubber slider / 96 Slider) - standard simulated shoe sole.

Top Surface	Dry Reading	Wet Reading
Standard Grit Surface	80	75

The Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians.

Four S Pendulum Value	Potential For Slip
Above 65	Extremely Low
35 to 65	Low
25 to 65	Moderate
25 and Below	High

To ensure that the above slip resistant levels are maintained the Flat Sheet should be kept clean in accordance with our cleaning guide and tips.