



# DINO GRIP STAIR TREADS

## Data Sheet

### DESCRIPTION

Dino Grip Stair Treads are a high-performance safety stair tread made from high quality FRP (Fiber Reinforced Plastic)/ GRP (Glass-fiber Reinforced Plastic)

### CHARACTERISTICS

- Slip Resistant Surface
- Impact Resistant
- Class 1 Flame Spread - Non-Sparking
- Corrosion Resistant
- Lightweight
- Non-Metallic
- Tough & Durable
- Choice of Nosing Color
- Choice of Sizes
- Quick Installation
- Manufactured to ISO 9001

### APPLICATIONS

Ideal for the installation on steps, fire escapes, all staircases, decking top surface, mezzanine floors and spiral staircases and for over-cladding onto worn surfaces.

### TECHNICAL DATA

Description	Slip Resistant Decking Profiles
Top Finish	Carbon and Silicon Grip Top Surface
Stock Colors	Black with Yellow Nosing/Brown with Black Nose/ Buff with Brown Nosing / Black with White Nosing
Thickness	Nominally 1/8 - 5/32 in Thick
Chemical Resistance	Different Chemical Resistance Available, Please Call our Technical Department for Advice
Panel Weight	2 ft x 13.5 in x 2 in - 4.9 lb
Service Temperatures	-4° f to + 176° f
Load capabilities	Credited with no load bearing strength
Design Life	10+ Years (subject to traffic analysis)
General Use	Standard Pedestrian Traffic

### SLIP RESISTANT LEVELS

Measured using the Pendulum test method (Four S rubber slider / 96 Slider) - standard simulated shoe sole.

Top Surface	Dry Reading	Wet Reading
Standard Grit Surface	80	75

The Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians.

Four S Pendulum Value	Potential For Slip
Above 65	Extremely Low
35 to 65	Low
25 to 65	Moderate
25 and below	High

To ensure that the above slip resistant levels are maintained the Stair Treads should be kept clean in accordance with the attached cleaning guide and tips.