



DINO GRIP ALUGRIP - SOCIAL DISTANCING FLOOR SIGNS

Data Sheet

Description

Richco Alugrip are custom designed foil-based social distancing flooring decals. They are hard-wearing with superior slip resistance and are suitable for interior / exterior installation.

Our decals have rounded edges to avoid peeling and are uv stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

We can add your company logo and colors to make the decals custom to your business and can ship within two business days of your order.

Characteristics

- Custom social distancing flooring decals.
- Add your company logos and colors.
- Trouble free, fast application. End users can install– does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days of your order.

Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Tile
- Laminates
- Brick
- Pavers
- Vinyl
- Commercial Grade Carpet
- Terrazzo

Application

Grocery stores, Convenience Stores, Hardware stores, Restaurants, Hotels, Hospitals, Car Parks, Shopping Malls, Stadiums, Amusement Parks, Universities, Side Walks, Curbside Pick-ups & Exterior Collection Points.

Technical Data

Description	Social Distancing Floor Queue Line Marking Kit
Material	Foil based media (FBM) film + texture + PSA + Release Liner = <20 mil. Material is pliable, lightweight, has no memory and will not shrink. Conforms to uneven surfaces.
Size	2ft x 2ft or 1ft x 1ft Circle or Square Floor Decal / Queue Line Marking Kit
Adhesive	Pressure sensitive, permanent acrylic, typically no residue when removed.
Liner	84# silicone based stay flat release liner.
Application	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
Usage	Outdoor & Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tarmac, tile, brick / pavers, stone, terrazzo, vinyl, laminate, marble and carpet flooring.
Life Expectancy	Printed and Installed up to 1 year with heavy pedestrian traffic and harsh weather.
Slip Resistance	Meets slip resistant standards, dry & wet: ANSI A137.1, UL 410, ASTM D2240-05, HB198:2014, British BS 7976-2/UKSRG, Australian AS 4586:2013 (app. D) = R11
Fire Rating	A-classification for surface burning test; ASTM E84-15b (NFPA 225, ANSI/UL 723, UBC 8-1).
Surface Reflective Reading	130 mcd (millicandelas) = 3.25 lux.
Temperature Range	Withstands high temperature range; -40°f - 302°f / -40°c - 150°c
Cleaning	Easily cleaned with hose and broom or gentle power washing
Harmonized Tariff Code	NCM: 7607.20.0000.
Shelf Life	2 Years stored at 70°f / 21°c and 50% relative humidity
Environmentally Friendly	Contains no PVC; dispose with aluminium recycling.
Country of Origin	Made in the USA