



DINO GRIP PLASTIGRIP - SOCIAL DISTANCING FLOOR SIGNS

Data Sheet

Description

Richco Plastigrip are custom designed foil-based social distancing flooring decals. They are hard-wearing with superior slip resistance and are suitable for interior installation on rigid surfaces.

Our decals have rounded edges to avoid peeling and are uv stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

We can add your company logo and colors to make the decals custom to your business and can ship them within two business days of your order.

Characteristics

- Custom social distancing flooring decals.
- Add your company logos and colors.
- Trouble free, fast application. End users can install– does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days or your order.

Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Vinyl
- Laminates
- Brick
- Pavers
- Tile
- Carpet
- Terrazzo

Applications

Ideal for one-step installation on exterior and rigid interior surfaces in areas such as:

- Grocery Stores
- Convenience Stores
- Hardware store
- Restaurants
- Hotels
- Shopping Malls
- Stadiums
- Amusement parks
- Universities
- Hospitals.

Technical Data

Description	Social Distancing Floor Queue Line Marking Kit
Material	Scratch Resistant, non-slip fabric floor material with no need for lamination.
Size	2ft x 2ft or 1ft x 1ft Circle or Square Floor Decal / Queue Line Marking Kit
Adhesive	Pressure sensitive, permanent acrylic, typically no residue when removed.
Thickness of Material	15 Mil / 240 GSM
Application	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
Usage	Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tile, brick / pavers, terrazzo, vinyl, laminate and carpet flooring.
Life Expectancy	Printed and Installed up to 1 year with heavy pedestrian traffic.
Slip Resistance	Meets slip resistant standards, dry & wet: ASTM D2047
Fire Rating	ASTM E-84
Harmonized Tariff Code	NCM: 7607.20.0000.
Shelf Life	2 Years stored at 70° f / 21° c and 50% relative humidity
Environmentally Friendly	Contains no PVC; dispose with aluminium recycling.
Country of Origin	Made in the USA