



# DINO GRIP STANDARD VINYL - SOCIAL DISTANCING FLOOR SIGNS

## Data Sheet

### Description

Richco Standard are custom designed foil-based social distancing flooring decals. They are hard-wearing with superior slip resistance and are suitable for interior installation on rigid surfaces.

Our decals have rounded edges to avoid peeling and are UV stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

We can add your company logo and colors to make the decals custom to your business and can ship within two business days of your order.

### Characteristics

- Custom social distancing flooring decals.
- Add your company logos and colors.
- Trouble free, fast application. End users can install— does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days of your order.

### Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Vinyl
- Laminates
- Brick
- Pavers
- Tile
- Carpet
- Terrazzo

### Applications

Ideal for one-step installation on exterior and rigid interior surfaces in areas such as:

- Grocery Stores
- Convenience Stores
- Hardware store
- Restaurants
- Hotels
- Shopping Malls
- Stadiums
- Amusement parks
- Universities
- Hospitals.

### Technical Data

<b>Description</b>	Social Distancing Floor Queue Line Marking Kit
<b>Material</b>	Specially formulated flexible vinyl.
<b>Size</b>	2ft x 2ft or 1ft x 1ft Circle or Square Floor Decal / Queue Line Marking Kit
<b>Adhesive</b>	Pressure sensitive, permanent acrylic, typically no residue when removed.
<b>Thickness of Material</b>	11 Mil
<b>Application</b>	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
<b>Usage</b>	Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tile, brick / pavers, terrazzo, vinyl, laminate, and carpet flooring.
<b>Water Resistance</b>	Good. Do not saturate.
<b>Humidity Resistance</b>	Excellent
<b>Solvent Resistance</b>	Excellent
<b>Life Expectancy</b>	Printed and Installed up to 6 months with heavy pedestrian traffic.
<b>Temperature Range</b>	Withstands high temperature range; 40° f - 90° f / -40° c - 32° c
<b>Harmonized Tariff Code</b>	NCM: 7607.20.0000.
<b>Shelf Life</b>	6 months stored at 70° f / 21° c and 50% relative humidity
<b>Environmentally Friendly</b>	Contains no PVC; dispose with aluminium recycling.
<b>Country of Origin</b>	Made in the USA