



DINO GRIP ALUGRIP - SOCIAL 6FT FLOOR STICKERS

Data Sheet

Description

Richco Elevator Floor Stickers are custom designed foil-based social distancing flooring Sticker. They are hard-wearing with superior slip resistance and are suitable for interior / exterior installation.

Our Strickers have rounded edges to avoid peeling and are uv stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

Each Sticker comes in a range of colors to make the decals custom to your business and can ship within two business days of your order.

Characteristics

- Trouble free, fast application. End users can install– does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days of your order.

Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Tile
- Laminates
- Brick
- Pavers
- Vinyl
- Commercial Grade Carpet
- Terrazzo

Application

Grocery stores, Convenience Stores, Hardware stores, Restaurants, Hotels, Hospitals, Car Parks, Shopping Malls, Stadiums, Amusement Parks, Universities, Side Walks, Curbside Pick-ups & Exterior Collection Points.

Technical Data

Description	6ft Floor Stickers
Material	Foil based media (FBM) film + texture + PSA + Release Liner = <20 mil. Material is pliable, lightweight, has no memory and will not shrink. Conforms to uneven surfaces.
Size	8" x 8" Round
Adhesive	Pressure sensitive, permanent acrylic, typically no residue when removed.
Liner	84# silicone based stay flat release liner.
Application	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
Usage	Outdoor & Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tarmac, tile, brick / pavers, stone, terrazzo, vinyl, laminate, marble and carpet flooring.
Life Expectancy	Printed and Installed up to 1 year with heavy pedestrian traffic and harsh weather.
Slip Resistance	Meets slip resistant standards, dry & wet: ANSI A137.1, UL 410, ASTM D2240-05, HB198:2014, British BS 7976-2/UKSRG, Australian AS 4586:2013 (app. D) = R11
Fire Rating	A-classification for surface burning test; ASTM E84-15b (NFPA 225, ANSI/UL 723, UBC 8-1).
Surface Reflective Reading	130 mcd (millicandelas) = 3.25 lux.
Temperature Range	Withstands high temperature range; -40°f - 302°f / -40°c - 150°c
Cleaning	Easily cleaned with hose and broom or gentle power washing
Harmonized Tariff Code	NCM: 7607.20.0000.
Shelf Life	2 Years stored at 70°f / 21°c and 50% relative humidity
Environmentally Friendly	Contains no PVC; dispose with aluminium recycling.
Country of Origin	Made in the USA