



DINO GRIP PLASTIGRIP - SOCIAL DISTANCING FLOOR LINES

Data Sheet

Description

Richco Social Distancing Floor Lines are custom designed foil-based social distancing flooring sticker. They are hard-wearing with superior slip resistance and are suitable for interior installation on rigid surfaces.

Our sticker has rounded edges to avoid peeling and are UV stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

Each sticker comes in a range of colors to make the decals custom to your business and can ship them within two business days of your order.

Characteristics

- Trouble free, fast application. End users can install— does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days of your order.

Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Vinyl
- Laminates
- Brick
- Pavers
- Tile
- Carpet
- Terrazzo

Applications

Ideal for one-step installation on exterior and rigid interior surfaces in areas such as:

- Grocery Stores
- Convenience Stores
- Hardware store
- Restaurants
- Hotels
- Shopping Malls
- Stadiums
- Amusement parks
- Universities
- Hospitals.

Technical Data

Description	Social Distancing Floor Lines
Material	Scratch Resistant, non-slip fabric floor material with no need for lamination.
Size	3ft x 3.5"
Adhesive	Pressure sensitive, permanent acrylic, typically no residue when removed.
Thickness of Material	15 Mil / 240 GSM
Application	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
Usage	Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tile, brick / pavers, terrazzo, vinyl, laminate and carpet flooring.
Life Expectancy	Printed and installed up to 1 year with heavy pedestrian traffic.
Slip Resistance	Meets slip resistant standards, dry & wet: ASTM D2047
Fire Rating	ASTM E-84
Harmonized Tariff Code	NCM: 7607.20.0000.
Shelf Life	2 Years stored at 70° f / 21° c and 50% relative humidity
Environmentally Friendly	Contains no PVC; dispose with aluminium recycling.
Country of Origin	Made in the USA