



# DINO GRIP STANDARD VINYL - FLOOR ARROW KIT

## Data Sheet

### Description

Richco Floor Arrow Kit are custom designed foil-based social distancing flooring sticker. They are hard-wearing with superior slip resistance and are suitable for interior Installation on rigid surfaces.

Our Stickers have rounded edges to avoid peeling and are uv stable with long-term durability. They are easy to install with no special equipment required - just clean and stick. They can easily be installed onto any surface and are easily removed with little or no residue.

Each Sticker comes in a range of colors to make the decals custom to your business and can ship within two business days of your order.

### Characteristics

- Trouble free, fast application. End users can install– does not require professional installers.
- Hardwearing & durable.
- Scratch resistant and will not tear.
- UV stable.
- Superior slip resistance and meets slip resistant standards.
- Rounded edges to avoid peeling.
- Typically leaves no residue upon removal.
- Shipped within two business days or your order.

### Suitable Surfaces

Can be installed onto any surface which includes:

- Concrete
- Vinyl
- Laminates
- Brick
- Pavers
- Tile
- Carpet
- Terrazzo

### Applications

Ideal for one-step Installation on exterior and rigid Interior surfaces in areas such as:

- Grocery Stores
- Convenience Stores
- Hardware store
- Restaurants
- Hotels
- Shopping Malls
- Stadiums
- Amusement parks
- Universities
- Hospitals.

### Technical Data

Description	Floor Arrow Kit
Material	Specially formulated flexible vinyl.
Size	<ul style="list-style-type: none"> <li>• 6ft Line Markings with Arrow either end.</li> <li>• 2 additional directional arrows - 12" x 3"</li> <li>• Text " Please stand 6ft Apart " Stay Safe"</li> </ul>
Adhesive	Pressure sensitive, permanent acrylic, typically no residue when removed.
Thickness of Material	11 Mil
Application	No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
Usage	Indoor floor surfaces (heavily textured & non-textured) including concrete (sealed & unsealed), tile, brick / pavers, terrazzo, vinyl, laminate, and carpet flooring.
Water Resistance	Good. Do not saturate.
Humidity Resistance	Excellent
Solvent Resistance	Excellent
Life Expectancy	Printed and Installed up to 6 months with heavy pedestrian traffic.
Temperature Range	Withstands high temperature range; 40° f - 90° f / -40° c - 32° c
Harmonized Tariff Code	NCM: 7607.20.0000.
Shelf Life	6 months stored at 70° f / 21° c and 50% relative humidity
Environmentally Friendly	Contains no PVC; dispose with aluminium recycling.
Country of Origin	Made in the USA